Packing Instruction | 1133I-R

PSN: UN1133, Adhesives, 3, PG II

Q1: Is each container > 1 L (0.3 gal) capacity? IF YES, Use this instruction. IF NO GO TO Q2.

Q2: Does package contain > 8 gallons (30 liters) of UN1133 liquids? IF YES, Use this instruction. IF NO GO TO Q3

Q3: Is total weight (ALL contents + packaging) GREATER than (>) 550 lbs? IF YES, USE THIS INSTRUCTION.

IF YOU ANSWERED 'NO' TO Q1, Q2, AND Q3, USE PACKING INSTRUCTION 1133I-LQ TO PACK/SHIP PRODUCT

MODE OF TRANSPORT PROHIBITIONS: Ground shipping: **ALLOWED** | NO AIR OR VESSEL SHIPPING IS PERMITTED W/O WRITTEN AUTHORIZATION FROM LIIHAZMAT@LENNOXINTL.COM. IF WRITTEN AUTHORIZATION IS GIVEN, LIMITS ARE: Passenger aircraft/rail: **ALLOWED 1.32 gal (5 L) limit** | Cargo aircraft: **ALLOWED 15.85 gal (60 L) limit** | Vessel: **ALLOWED, Stowage Category B**

MATERIALS OF TRADE EXCEPTION - MAY BE SOLD BY LENNOX STORES TO TRADESMEN IN QUANTITIES NOT TO EXCEED A TOTAL OF 8 GAL (30 LITERS) OF PRODUCT <u>UNLESS</u> tradesmen shows proof of commercial drivers license (CDL) with hazardous materials /dangerous goods endorsement. If tradesman has endorsed CDL, sales volume limits do not apply.

CONTAINER & PACKAGING REQUIREMENTS

ENN


ТΕ

RNATIONAL

- Use strong outer packaging appropriate for weight of contents (i.e. box must be rated for the maximum weight being placed in the box). If you cannot tell the weight rating of the box, please ask your supervisor and/or contact Lennox Environmental at liihazmat@lennoxintl.com or +1-972-497-7532.
 - Add separation materials to prevent damage to containers AND hold upright.
 - Cardboard packing box must have a **PREPRINTED** UN symbol on it, and a rating of 4GV/X5/S, 4GV/X7/S, or 4G/Y24.2/S. IF A BOX IS REQUIRED to ship this product. If you do not have a U/N certified box contact your supervisor, you may not use a non-U/N certified box to ship this product.
 - Box must be labeled with the Class 3 Flammable Liquid Label on two opposite sides of box. NEVER PUT LABELS ON TOP OR BOTTOM OF BOX.
 - Place the Consigner (Shipper/From) / Consignee (Receiver/To) on box with weather resistant marking.
 - Orientation Arrow is required for this UN number in correct direction (UP) on two OPPOSING SIDES of the box.
- Box must be marked with "UN1133" and "Adhesives, containing flammable liquid" within 6 inches of labels in
 - If you are putting an inner package/boxholding this product inside an outer box or on a pallet (i.e. using an 'overpack'), inner boxes MUST MEET THIS PACKING INSTRUCTION. AND, outer box or pallet shrink wrap MUST BE MARKED and LABELED with every marking/label used on the inner boxes if not visible through the overpack. Outer box must have the OVERPACK marking.

An 'overpack' is a container (box, shrink-wrapped pallet, etc.) used to consolidate individual containers in an easier to ship form.





FOR QUESTIONS OR WAIVERS PLEASE CONTACT LIIHAZMAT@LENNOXINTL.COM



4

8

DO NOT SHIP UN1133 WITHOUT SEPARATION IN THE VEHICLE WITH THESE CLASSES





© 2022 Thrival Company

86

Packing Instruction | 1133I-LQ

PSN: UN1133, Adhesives, 3, PG II, Ltd Qty

Q1: Is each container 1 L (0.3 gal) or less capacity? IF YES then GOTO Q2, IF NO, USE PI 1133I-R.

Q2: Does package contain < 8 gallons (30 liters) of UN1133 liquids? IF YES GOTO Q3. IF NO, USE PI1133I-R.

Q3: Is total weight (ALL contents + packaging) LESS than (<) 550 lbs? IF YES, USE THIS INSTRUCTION. IF NO, USE PI-1133I-R.

IF YOU ANSWERED 'YES' TO Q1, Q2, AND Q3, USE THIS PACKING INSTRUCTION TO PACK/SHIP PRODUCT

MODE OF TRANSPORT PROHIBITIONS: Ground shipping: ALLOWED | Passenger aircraft/rail: ALLOWED 1.32 gal (5 L) limit | Cargo aircraft: ALLOWED 15.85 gal (60 L) limit | Vessel: ALLOWED, Stowage Category B

MATERIALS OF TRADE EXCEPTION - MAY BE SOLD BY LENNOX STORES TO TRADESMEN IN QUANTITIES NOT TO EXCEED A TOTAL OF 8 GAL (30 LITERS) OF PRODUCT UNLESS tradesmen shows proof of commercial drivers license (CDL) with hazardous materials /dangerous goods endorsement. If tradesman has endorsed CDL, sales volume limits do not apply.

CONTAINER & PACKAGING REQUIREMENTS

RNATIONA

Use strong outer packaging appropriate for weight of contents (i.e. box must be rated for the maximum weight being placed in the box). If you cannot tell the weight rating of the box, please ask your supervisor and/or contact Lennox Environmental at liihazmat@lennoxintl.com or +1-972-497-7532.

Add separation materials to prevent damage to containers AND hold upright.

Box must be marked with the Limited Quantity (LQ) marking on one side of box. Place the Consigner (Shipper/From) / Consignee (Receiver/To) on box with weather resistant marking.

Orientation Arrow is required for this UN number in correct direction (UP) on two OPPOSING SIDES of the box.

If you are putting an inner package/box holding this product inside another box or on a pallet (i.e. using an 'overpack'), inner boxes MUST MEET THIS PACKING INSTRUCTION. **AND**, outer container or shrink wrap MUST BE MARKED and LABELED with every marking/label used on the inner boxes if not visible through the overpack. **Outer box must have the OVERPACK marking**.


An 'overpack' is a container (box, shrink-wrapped pallet, etc.) used to consolidate individual containers in an easier to ship form.

Weigh the completed package once all items have been added. Verify max gross weight of the package DOES NOT EXCEED 550 lbs (249.48 kg). If weight exceeds 550 pounds you must use PI-1133I-R for fully regulated hazardous materials packing instructions instead.

WARNING- If liihazmat@lennoxintl.com approves IN WRITING shipping by air or rail, you must add <u>this label to two OPPOSITE sides of box</u> (in addition to the LQ label) and not exceed the quantity limits under MODE OF TRANSPORT PROHIBITIONS listed above. IATA shipping papers are required for AIR SHIPPING.


SHIPPING PAPER CHECK IS REQUIRED Before providing shipping papers to a carrier, you must verify the product description on the shipping paper (bill of landing) is correct. If your package weighs 550 pounds (lbs) or less, you must add ", Ltd Qty" to the shipping paper using a pen after the description located in the SEE !!WARNING!! IMAGE. PACKAGE WEIGHT: By legal definition includes all contents including hazardous materials in one container or on a pallet yielding a TOTAL weight of shipment (not just individual hazardous material weight).

2





!! SHIPPING PAPER WARNING !! ADD ", LTD QTY" ON ANY SHIPMENT LBS OR LESS



AIR CONDITIONERS, FURNACES, SOLAR HEATING AND COOLING EQUIPMENT, AND MATERIALS EQUIPMENT, AND SUPPLIES USED IN THE MANUFACTURE, SALE, AND DISTRIBUTION THEREOF.

OXIDIZER

FOR QUESTIONS OR WAIVERS PLEASE CONTACT LIIHAZMAT@LENNOXINTL.COM

44

POISON

TOXIC



5

6

DO NOT SHIP UN1133 IN THE SAME VEHICLE WITH THESE CLASSES

EXPLOSIVES

EXPLOSIVES

DO NOT SHIP UN1133 WITHOUT SEPARATION IN THE VEHICLE WITH THESE CLASSES

TOXIC



© 2022 Thrival Company