

Q1: Is each container > 1 L capacity? IF YES, Use this instruction. IF NO GO TO Q2.

Q2: Is the aerosol can charged to > 1241.1 kPa at 54.4°C ? IF YES, Use this instruction. IF NO GO TO Q3.

Q3: Is total weight (ALL contents + packaging) GREATER than (>) 30 kg? IF YES, Use this instruction.

IF YOU ANSWERED 'NO' TO Q1, Q2, AND Q3, USE PACKING INSTRUCTION CA 1950ANE-LQ TO PACK/SHIP PRODUCT





MODE OF TRANSPORT PROHIBITIONS: NO AIR OR VESSEL SHIPPING IS PERMITTED W/O WRITTEN AUTHORIZATION FROM LIIHAZMAT@LENNOXINTL.COM. IF WRITTEN AUTHORIZATION IS GIVEN, LIMITS ARE: Ground shipping: **ALLOWED 75 L limit** | Passenger Rail: **ALLOWED 75 L limit** | Passenger aircraft: **ALLOWED 75 kg limit** | Cargo aircraft: **ALLOWED 150 kg limit** | Vessel: **ALLOWED, Stowage Category B**

AEROSOLS CONTAINERS AND GAS CARTRIDGES FOR TRANSPORT OF DANGEROUS GOODS MUST HAVE A STRONG OUTER PACKAGING SUCH THAT THE GROSS MASS OF EACH OUTER PACKAGING BE LESS THAN OR EQUAL TO 30 kg.

CONTAINER & PACKAGING REQUIREMENTS

- ① Use strong outer packaging appropriate for weight of contents (i.e. box must be rated for the maximum weight being placed in the box). If you cannot tell the weight rating of the box, please ask your supervisor and/or contact Lennox Environmental at liihazmat@lennoxintl.com or +1-972-497-7532.
- ② Protect valves from leaking or damage by wrapping, using a cap, or other protective devices. If for any reason, wrapping, caps and protective devices are not available or practical, exemptions may apply. Contact LIIHazmat@lennoxintl.com for a waiver.
- ③ Add separation materials to prevent damage to containers AND hold upright.
- ④ Cardboard packing box must have a PREPRINTED UN symbol on it, and a rating of U/N 4GV/X5/S or U/N 4GV/X7/S IF A BOX IS REQUIRED to ship this product. If you do not have a U/N certified box contact your supervisor, you may not use a non-U/N certified box to ship this product.
- ⑤ Box must be labeled with the Class 2 Non-Flammable Gas Label on two opposite sides of box. NEVER PUT LABELS ON TOP OR BOTTOM OF BOX.
- ⑥ Place the Consigner (Shipper/From) / Consignee (Receiver/To) on box with weather resistant marking.
- ⑦ No Orientation Arrow is required for this UN number.
- ⑧ Box must be marked with "UN1950" and "Aerosols, non-flammable, (each not exceeding 1 L capacity)" within 15 centimeters of labels in ⑤
- ⑨ If you are putting an inner package/box holding this product inside an outer box or on a pallet (i.e. using an 'overpack'), inner boxes MUST MEET THIS PACKING INSTRUCTION. **AND**, outer box or pallet shrink wrap MUST BE MARKED and LABELED with every marking/label used on the inner boxes if not visible through the overpack. **Outer box must have the OVERPACK marking.**



An 'overpack' is a container (box, shrink-wrapped pallet, etc.) used to consolidate individual containers in an easier to ship form.

NO ERAP INDEX # || FOR QUESTIONS OR WAIVERS PLEASE CONTACT LIIHAZMAT@LENNOXINTL.COM

DO NOT SHIP UN1950AN IN THE SAME VEHICLE WITH THESE CLASSES



NO SEPARATION RESTRICTIONS APPLY

Q1: Is each container 1 L capacity or less? IF YES, GO TO **Q2**, IF NO, USE PI-CA 1950ANE-R TO PACK/SHIP.

Q2: Is the aerosol can charged to 1241.1 kPa or less at 54.4°C? IF YES, GO TO **Q3**, IF NO, USE PI-CA 1950ANE-R TO PACK/SHIP.

Q3: Is total weight (ALL contents + packaging) LESS than (<) 30 kg? IF YES, Use this instruction.

IF YOU ANSWERED 'NO' TO Q1, Q2, AND/OR Q3, USE PACKING INSTRUCTION CA 1950ANE-R TO PACK/SHIP THIS PRODUCT.




MODE OF TRANSPORT PROHIBITIONS: Ground shipping: **ALLOWED 75 L limit** | Passenger Rail: **ALLOWED 75 L limit** | Passenger aircraft: **ALLOWED 30 kg limit** | Cargo aircraft: **ALLOWED 150 kg limit** | Vessel: **ALLOWED, Stowage Category A**

AEROSOLS CONTAINERS AND GAS CARTRIDGES FOR TRANSPORT OF DANGEROUS GOODS MUST HAVE A STRONG OUTER PACKAGING SUCH THAT THE GROSS MASS OF EACH OUTER PACKAGING BE LESS THAN OR EQUAL TO 30 kg.

CONTAINER & PACKAGING REQUIREMENTS

- ① **Use strong outer packaging** appropriate for weight of contents (i.e. box must be rated for the maximum weight being placed in the box). If you cannot tell the weight rating of the box, please ask your supervisor and/or contact Lennox Environmental at liihazmat@lennoxintl.com or +1-972-497-7532.
- ② **Protect valves from leaking or damage by wrapping**, using a cap, or other protective devices. If for any reason, wrapping, caps and protective devices are not available or practical, exemptions may apply. Contact LIHazard@lennoxintl.com for a waiver.
- ③ **Add separation materials** to prevent damage to containers AND hold upright.
- ④ **Box must be marked with the Limited Quantity (LQ) marking** on one side of box.
- ⑤ **Place the Consigner (Shipper/From) / Consignee (Receiver/To) on box** with weather resistant marking.
- ⑥ **No Orientation Arrow is required for this UN number.**
- ⑦ **If you are putting an inner package/box** holding this product inside another box or on a pallet (i.e. using an 'overpack'), inner boxes MUST MEET THIS PACKING INSTRUCTION. **AND**, outer container or shrink wrap MUST BE MARKED and LABELED with every marking/label used on the inner boxes if not visible through the overpack. **Outer box must have the OVERPACK marking.**
- ⑧ **Weigh the completed package once all items have been added.** Verify max gross weight of the package DOES NOT EXCEED 30 kg. If weight exceeds 30 kilograms you must use PI-CA 1950ANE-R for fully regulated hazardous materials packing instructions instead.



An 'overpack' is a container (box, shrink-wrapped pallet, etc.) used to consolidate individual containers in an easier to ship form.

WARNING- If liihazmat@lennoxintl.com approves IN WRITING shipping by air or rail, you must add **this label to two OPPOSITE sides of box** (in addition to the LQ label) and not exceed the quantity limits under **MODE OF TRANSPORT PROHIBITIONS** listed above. IATA shipping papers are required for AIR SHIPPING.

SHIPPING PAPER CHECK IS REQUIRED Before providing shipping papers to a carrier, you must verify the product description on the shipping paper (bill of lading) is correct. If your **package** weighs 30 kilograms (kg) or less, you must add "**, Ltd Qty**" to the shipping paper using a pen after the description located in the **SEE !!WARNING!! IMAGE. PACKAGE WEIGHT:** By legal definition includes all contents including hazardous materials in one container or on a pallet yielding a TOTAL weight of shipment (not just individual hazardous material weight).

!! SHIPPING PAPER WARNING !!
ADD ", LTD QTY" ON ANY SHIPMENT 30 kg OR LESS

Descriptions of articles	special marks and Exceptions
***** DANGEROUS GOODS *****	(X.X kg)
UN1950, Aerosols, non-flammable, 2.1, Ltd Qty	←
AIR CONDITIONERS, FURNACES, SOLAR HEATING AND COOLING EQUIPMENT, AND MATERIALS EQUIPMENT, AND SUPPLIES USED IN THE MANUFACTURE, SALE, AND DISTRIBUTION THEREOF.	

NO ERAP INDEX # || FOR QUESTIONS OR WAIVERS PLEASE CONTACT LIHAZMAT@LENNOXINTL.COM

DO NOT SHIP UN1950AN IN THE SAME VEHICLE WITH THESE CLASSES



NO SEPARATION RESTRICTIONS APPLY